



TG82R AND TG103R PRODUCT LINES

CLEANING INSTRUCTIONS FOR SEALED SURFACE KEYBOARDS:

1. Unplug the keyboard and clean the surface of the product by lightly spraying, wiping, or gently brushing. Use only cloth rags, sponges, or brushes with soft bristles.

****DO NOT SUBMERGE THE KEYBOARD OR PLACE THE *USB* OR *PS/2* CONNECTOR INTO THE CLEANING SOLUTION****

2. For drying, wipe with a soft dry cloth or allow to air dry.

RECOMMENDED DISINFECTANTS:

- Alcohol based cleaning products
- Phenol based cleaning products
- Chlorine based cleaning products
- 10% Bleach solution
- 70% Isopropyl Alcohol solution
- 10% Hydrogen Peroxide
- Disinfectant Wipes
- Soap and water

DO NOT USE:

- Petroleum based cleaning fluids, such as Gasoline
- Acetone
- Over 10% bleach solutions
- Temperature or pressure sterilization
- Abrasive scrubbing pads

THIS DOCUMENT IS TO ADVISE THE PROPER METHODS FOR CLEANING YOUR SEALED SURFACE KEYBOARD. *TG-3 ELECTRONICS, INC.* CANNOT ASSUME ANY RESPONSIBILITY FOR THE APPLICATION OF THESE INSTRUCTIONS OR THE DISINFECTANTS LISTED ON THIS DOCUMENT. IF THERE ARE ANY QUESTIONS, PLEASE CONTACT *TG-3 ELECTRONICS, INC.* PRIOR TO CLEANING.

TG-3 ELECTRONICS, INC.
4615 – 70TH AVE.
KENOSHA, WI 53144

PHONE: 262.652.2626 FAX: 262.652.2121
www.tg3electronics.com