



20 KEY BUMP BAR

Designed for Kitchen Video System Applications

SPECIFICATIONS

- Storage Temperature: -40C to +70C
- Operating Temperature: OC to +70C
- Dimensions: 9.96 x 2.96 x 1.05 in (253 x 75 x 27 mm)
- Weight: Max 1.55 lbs (0.703 kg)

CUSTOMIZATION

- Color
- Legends
- Interfaces
- Company Logos
- More Options Available Upon
- More Options Available Upon Request

FEATURES

- 20 Key Sealed Membrane Input Surface
- Interfaces With Current Kitchen Video System
- Tuff-Key Technology
- High Quality and Durable
- Easy Installation
- Relegendable Quick and Easy to Change
- Mechanical Key Switches for Dependable, Durable Operation
- Splash / Spill Proof Design Provides Protection to its Components
- Standard and Custom Mounting Solutions Available
- Top or Side Mounting Antenna Configuration
- 50 Million Actuations Per Key

INTERFACE

- Wired: USB, PS2, RS232
- Wireless: Custom Wireless Protocol Between Transmitter and Receiver

TG3 PART NUMBER	DESCRIPTION
KBA-BB20-WR-TS-HOR	Wireless, Duraswitch, Receiver RS232, Horizontal
KBA-BB20-WR-TU-HOR	Wireless, Duraswitch, Receiver USB, Horizontal
KBA-BB20-WR-TP-HOR	Wireless, Duraswitch, Receiver PS2, Horizontal
KBA-BB20-WT-T-HOR	Wireless, Duraswitch, Transmitter, Horizontal
KBA-BB20-TE-TS-HOR	Tethered, Duraswitch, RS232, Horizontal
KBA-BB20-TE-TU-HOR	Tethered, Duraswitch, USB, Horizontal
KBA-BB20-TE-TP-HOR	Tethered, Duraswitch, PS2, Horizontal
KBA-BB20-WR-TS-VER	Wireless, Duraswitch, Receiver RS232, Vertical
KBA-BB20-WR-TU-VER	Wireless, Duraswitch, Receiver USB, Vertical
KBA-BB20-WR-TP-VER	Wireless, Duraswitch, Receiver PS2, Vertical
KBA-BB20-TE-TS-VER	Wireless, Duraswitch, Transmitter, Vertical
KBA-BB20-TE-TS-VER	Tethered, Duraswitch, RS232, Vertical
KBA-BB20-TE-TU-VER	Tethered, Duraswitch, USB, Vertical
KBA-BB20-TE-TP-VER	Tethered, Duraswitch, PS2, Vertical